

# jQuery 1.2 CheatSheet

SELECTORS	EVENTS	CORE UI EFFECTS	AJAX
#id, tag, .class, *	<b>HANDLERS</b>	<b>SHOW / HIDE</b>	<b>Request ( url, data, callback )</b>
elm1, elm2, elmN	.bind(type, data, fn)	.show()	\$.ajax(options)
ancestor descendant	.one(type, data, fn)	.show(speed, callback)	.load(u,d,c)
parent > child	.trigger(type, data)	.hide()	\$.get(u,d,c)
parent/ child	.triggerHandler(type, data)	.hide(speed, callback)	\$.getJSON(u,d,c)
prev + next	.unbind(type, data)	.toggle()	\$.getScript(u,c)
prev ~ siblings			\$.post(u,d,c)
	<b>MOUSE</b>	<b>ANIMATE</b>	.loadModified(u,d,c)
:first, :last	.mousedown(fn)	.stop()	
:not(selector)	.mousemove(fn)	.queue()	<b>Event Handler ( callback )</b>
:even, :odd	.mouseout(fn)	.queue(callback)	.ajaxComplete(c)
:eq(index)	.mouseover(fn)	.queue(queue)	.ajaxSend(c)
:gt(index)	.mouseup(fn)	.dequeue()	.ajaxStop(c)
:lt(index)		.animate(params, duration, easing, callback)	.ajaxError(c)
	<b>WINDOW</b>	.animate(params, options)	.ajaxStart(c)
:contains(text)	.load(fn)		.ajaxSuccess(c)
:empty	.scroll(fn)		
:has(selector)	.resize(fn)	<b>FADE</b>	<b>Serialize</b>
:parent		.fadeIn(speed, callback)	.serialize()
	<b>ERROR</b>	.fadeOut(speed, callback)	.serializeArray()
E[@attr]	.error()	.fadeTo(speed, opacity, c)	.ajaxSetup( options )
E[@attr=val]	.error(fn)		
E[@attr^=val] (begins)		<b>TRAVERSING</b>	<b>MANIPULATING</b>
E[@attr\$=val](ends)	<b>KEYBOARD</b>	<b>FILTER</b>	<b>INSIDE ( content )</b>
E[@attr*=val](contains)	.keydown()	.hasClass(class)	.append(c)
E[@attr=val][@attr=val](both)	.keydown(fn)	.filter(expr)	.appendTo(c)
	.keypress()	.filter(fn)	.prepend(c)
:nth-child(index)	.keypress(fn)	.is(expr)	.prependTo(c)
:first-child	.keyup()	.map(callback)	
:last-child	.keyup(fn)	.net(expr)	<b>OUTSIDE ( content )</b>
:only-child		.slice(start, end)	.after(c)
	<b>PAGE</b>		.before(c)
:enabled	.ready(fn)	<b>FIND ( expr )</b>	.insertAfter(c)
:disabled		.add(e)	.insertBefore(c)
:checked	<b>INTERACTION</b>	.children(e), .siblings(e)	
:selected	.hover(fnIN, fnOUT)	.contents()	<b>AROUND</b>
	.toggle(fnIN, fnOUT)	.find(e)	.wrap(html), .wrap(element)
:hidden	.blur(), .blur(fn)	.next(e), .nextAll(expr)	.wrapAll(html)
:visible	.change(), .change(fn)	.parent(e), .parents(e)	.wrapAll(element)
:header	.click()	.prev(e), prevAll(e)	.wrapInner(html)
:animated	.click(fn)		.wrapInner(element)
	.dblclick()	<b>ACCESS</b>	
:input	.dblclick(fn)	.each(callback)	<b>REPLACE</b>
:text	.focus()	.size()	.replaceWith(c)
:password	.focus(fn)	.length	.replaceAll(selector)
:radio	.select()	.get()	
:checkbox	.select(fn)	.get(index)	<b>CLEAR</b>
:submit	.submit()	.index(subject)	.empty()
:image	.submit(fn)		.remove(expression)
:reset	.unload()	<b>CHAIN</b>	
:button	.unload(fn)	.andSelf()	<b>CLONE</b>
:file	.unblur()	.end()	.clone() .clone(true)
:hidden	.unblur(fn)		
<b>CSS</b>	<b>ATTRIBUTES</b>	<b>HTML</b>	
.css(name, value)	.addClass(class)	.attr(name)	.html()
.css(properties)	.removeClass(class)	.attr(key, value)	.html(value)
		.attr(properties)	.text()
.height(value)	.toggleClass(class)	.attr(key, function)	.text(value)
.width(value)	.offset()	.removeAttr(name)	.val(value)